

CeraZorb HD (HIGH DENSITY) - 10MM



ACOUSTICAL UNDERLAYMENT FOR SETTING CERAMIC TILE, NATURAL STONE & CLICK LVT FLOORING

Cerazorb is a lightweight underlayment system that has been specially designed for ceramic tile, natural stone and click LVT flooring. Cerazorb offers high energy impact with low weight and will remain unchanged after repeated impact loads.

Cerazorb is an underlayment made out of hemi-crystalline thermoplastic that will not rot, swell, absorb water and is anti-microbial. Cerazorb has been tested and has the performance equal to 1/2" natural cork at a much lower price. Cerazorb can be bonded to approved sub floors using Impacta T-440 bond coat adhesive.

TECHNICAL DATA

- Thickness: 10mm-3/8"
- Sheet Size: 4' x 4'
- Quantity per package: 12 sheets/192 sq. ft.
- Weight per package: 28 lbs
- Delta IIC 23 on a 6" concrete slab
- Operating temperature range: -20°F-210°F
- Can be used with radiant heat systems

BENEFITS

- Up to 25 times lighter than 1/4" backer board
- "Synthetic cork product" **will not** rot, support mold & mildew or absorb moisture
- Lightweight and easy to carry
- Credible acoustical performance
- Passes Robinson test to light commercial rating
- Credible acoustical and crack suspension

