

Acoustical Underlayment for Carpet & Carpet Tile

Superfloor® acoustical carpet underlayment is a premium carpet pad designed for use under carpet and carpet tiles. Most carpet pads are made from foam or rubber and deteriorate very fast causing wear paths and wear spots in the carpet in areas of high traffic. Superfloor is different than any other carpet pad in the market today offering glue down or traditional carpet tack installation.

Superfloor underlayments are designed to prolong the life of your carpet, while providing superior sound ratings for impact foot traffic noise. Superfloor carpet pads will not wear out like traditional carpet pads do.

Superfloor carpet pad underlayment is a 100% natural wood product made from recycled materials. Superfloor carpet underlayment is easily installed under carpet with carpet tacks or can be glued down.

Superfloor can also be installed under commercial carpet and is perfect for schools, classrooms and dormitories.



Benefits of Using Superfloor

- Excellent Sound Reducing performance for both commercial & residential carpet
- Economical system that is easy & fast to install, reducing installation & labor costs
- Environmentally friendly - bio-degradable
- Outstanding thermal qualities
- Moisture & mold resistant
- Extends life of carpet - will not collapse like foam padding - maintains acoustic performance

Product Specification:



Total thickness	7 mm / 1/4"
Board Size	23 1/4" x 33 7/8"
Boards per package	20 ea
Quantity per package	109 sq ft
Weight - sq ft	.375 lbs per sq ft
Weight per package	41 lbs

Acoustics performance on back page

Distributed by:

Superfloor Acoustical Testing

Note: The Δ IIC is a new ASTM test that measures the improvement in decibels. Example a Δ IIC 25 would mean a 25 point improvement. The Δ IIC test is only tested on a 6" concrete slab with no ceiling below.

Description	Detail	IIC / FIIC Rating
<p>Superfloor</p> <p>5/16" Carpet loose laid over 7mm Superfloor over 6" slab</p>		<p>Δ 34</p>
<p>Superfloor</p> <p>5/16" Carpet glued down over 7mm Superfloor over 6" slab</p>		<p>Δ 37</p>

For more information on Superfloor Underlay including installation instructions, installation videos, accessories and technical data please go online at www.Super-Floor.com or call us toll free at 800-569-1294