



- ◆ **High Tackability**
- ◆ **Class A fire rated**
- ◆ **Standard, designer or C.O.M. fabric**

Sound Quality® Acoustical Wall Panels by Sound Seal® are the solution for areas that require noise reduction and are available in a variety of models for various applications. The **S-3100** Wall Panel is manufactured specifically as a tack panel and offers minimal sound absorption. Application for the S-3100 panels includes conference rooms, classrooms, offices and any area where low absorption and high tackability is required.



The S-3100 panel is constructed with a 24# PCF mineral fiber core. Edges are fully wrapped in standard, custom or C.O.M. fabric with the option of square or bevel edge detail. Panels are available in ½" or ¾" thick with standard or custom sizes up to a maximum of 4' x 8'.

S-3100 panels are easily installed with nails & construction adhesive, mechanical clips or hoop & loop.

S-3100

TACKABLE
WALL PANELS



Finishes

Guilford of Maine FR701 Style 2100 is standard. Hundreds of approved decorator fabrics are also available from numerous manufacturers including, but not limited to: Guilford of Maine, Deepa Textiles, Design Tex, Wolf Gordon, Momentum and Knoll. Customers may also specify their own fabric, provided the material meets manufacturing requirements.

Mounting Options



Adhesive


Acoustical

NRC Rating


1/2"20
3/4" (perforated)60

Test data available upon request

Edge Detail



Square



Bevel

Fire Rating

All components shall have a Class A fire rating per ASTM E-84.

Specifications

Specifications can be downloaded from our website www.soundseal.com or call us at 1-800-569-1294.

Sound Seal® and Sound Quality® are registered trademarks of United Process, Inc.
©2003 United Process, Inc.