

**Spec Data Sheet SQ-107**



- ◆ **Excellent absorption rating**
- ◆ **Extreme abuse panels**
- ◆ **Class A fire rated**



**Sound Quality®** Acoustical Wall Panels by Sound Seal® are the solution for areas that require noise reduction and are available in a variety of models for various applications. The **S-4100** Wall Panel is manufactured specifically as an extreme abuse absorber panel that offers both excellent absorption and high durability. Application for the S-4100 panels includes gymnasiums, schools, universities, prisons, recreation centers and any area where excess reverberation and high abuse resistance is required.

S-4100 Extreme-Abuse Wall Panels are manufactured using a high impact fire rated perforated rigid PVC vinyl sheet with edges that are bent & welded to provide protection over the 1" or 2" fiberglass absorber. Panels are available in 20+ standard colors with custom color available. S-4100 panels are available in 1½" and 2⅝" thickness with sizes up to a maximum of 4' x 8'.

S-4100 panels can be quickly installed using a 2 part mechanical clip.

**S-4100**

EXTREME ABUSE  
WALL PANELS

Spec Data Sheet **SG-107**

**Finishes**



Rigid PVC vinyl is available in the following stock colors, other colors are available but minimums may apply. Consult factory for line card.

\*color may vary slightly from actual material

**Mounting Options**



**2-part  
Mechanical  
Clips**


**Acoustical**

NRC Rating

1 1/16"	.....	.080 - 0.90
2 1/16"	.....	.090 - 1.00

Test data available upon request

**Edge Detail**



**Square**

**Fire Rating**

All components shall have a Class A fire rating per ASTM E-84.

**Specifications**

Specifications can be downloaded from our website [www.soundseal.com](http://www.soundseal.com) or call us at 1-800-569-1294.

Sound Seal® and Sound Quality® are registered trademarks of United Process, Inc. ©2003 United Process, Inc.