



- Standard size 2' x 2' or 2' x 4'
- Custom sizes available
- 1" or 2" thickness
- 2 mil white pebble grain finish
- Excellent acoustical values
- Offered with a vinyl noise barrier for high STC requirements



50 H.P. Almgren Drive
Agawam, MA 01001

www.soundseal.com

Email: sales@soundseal.com

Tel: 800.569.1294

Fax: 413.789.4444

C-100 & C-100B

ACOUSTICAL CEILING TILES

Sound Quality® Ceiling tiles are offered as both a sound absorbing as well as a combination sound absorbing/sound blocking tile.

C-100 Ceiling Tiles have a 2 mil white pebble grain vinyl facing attached to a 1" or 2" thick rigid fiberglass board and have excellent sound absorption (NRC) ratings.

C-100B Ceiling Tiles take the standard C-100 tile and add a 1# per square foot foil backed vinyl noise to the backside of the tile for high sound absorption (NRC) and high sound blocking (STC) requirements.

FINISH

2 mil white pebble grain vinyl

ACOUSTICAL

NRC Rating

1" Thick _____ .85

2" Thick _____ 1.15

C-100B Version _____ STC 26

SUBSTRATE

6-7# PCF rigid fiberglass core

*C-100B adds a vinyl noise barrier

EDGE DETAIL

Square

WEIGHTS

C-100 Tile .6 lbs/SqFt

C-100B Tile 1.6 lbs/SqFt

MOUNTING OPTIONS

Grid supplied by others

SPECIFICATIONS

Specifications can be downloaded from our website

www.soundseal.com or call us at **1.800.569.1294**