



ACOUSTICAL UNDERLAYMENT FOR FLOATED & GLUE DOWN WOOD FLOORING

Cerazorb is a lightweight underlayment system that has been specially designed for floated or glue down wood flooring. Cerazorb offers high energy impact with low weight and will remain unchanged after repeated impact loads.

Cerazorb is an underlayment made out of hemi-crystalline thermoplastic that will not rot, swell, absorb water and is anti-microbial. Cerazorb has been tested and has the performance equal to 1/2" natural cork at a much lower price. Cerazorb can be bonded to approved sub floors using Impacta T-950 bond coat adhesive.

TECHNICAL DATA

- Thickness: 5 mm–3/16"
- Sheet Size: 4' x 4'
- Quantity per package: 25 sheets/400 sq. ft.
- Weight per package: 28 lbs
- R Value: 1.5
- Delta IIC 22 on a 6" concrete slab
- Operating temperature range: -20°F–210°F

BENEFITS

- Up to 25 times lighter than 1/4" backer board
- "Synthetic cork product" **will not** rot, support mold & mildew or absorb moisture
- Lightweight and easy to carry
- Credible acoustical performance



50 H.P. Almgren Drive
Agawam, MA 01001

www.soundseal.com
Email: sales@soundseal.com
Tel: 800.569.1294
Fax: 413.789.4444

