

WOODTRENDS
BY SOUND SEAL

TIMBER-STIX®
PRODUCT DATA SHEET

FEATURES

- Quick & easy installation
- Application on walls or ceilings
- Cut to size in field
- Built-in spacers
- Easy to handle
- Linear design
- Choice of 6 woodgrain veneers

SPECIFICATIONS

- **Panel Size:** 24" x 96"
- **Thickness:** 0.87"
- **Weight:** 27 lbs / panel
- **Fire Rating:** Class B per ASTM E-84-21a

INSTALL METHODS

- **Wall:** Furring strip, direct with screws & adhesive
- **Ceiling:** Furring strip



MAKE A STATEMENT.

YOU ONLY GET ONE CHANCE TO MAKE A FIRST IMPRESSION.
WITH TIMBER-STIX, IT'S ALWAYS A GOOD ONE.

COMPOSITION

- **Facing:**
  - Wood-veneered MDF board
- **Backing:**
  - 100% Polyethylene Terephthalate (PET)
  - 55% recycled content

ENVIRONMENTAL FACTORS

- PET is 100% recyclable
- Low VOC emissions
- ASTM — D51116
- LEED — MRc4

Red List Free · RoHS COMPLIANT · REACH COMPLIANT

VENEER OPTIONS



Ash	Light Oak	Walnut	Cherry	Dark Oak	Grey Oak
PET Backer: Light Camel	PET Backer: True Black	PET Backer: True Black	PET Backer: Pure Camel	PET Backer: True Black	PET Backer: True Black

PET Felt Backing*



True Black · Light Camel · Pure Camel

*PET backing colors shown for reference only and are not interchangeable. See above for veneer and backer color combinations.

ACOUSTICAL DATA

1/3 Octave Sound Absorption Coefficients at the Octave Band Frequencies							
Frequency (Hz)	**125**	**250**	**500**	**1K**	**2K**	**4K**	**NRC**
	0.08	0.08	0.29	0.70	1.07	0.83	0.55

Type "A" mount – flat

1/3 Octave Sound Absorption Coefficients at the Octave Band Frequencies							
Frequency (Hz)	**125**	**250**	**500**	**1K**	**2K**	**4K**	**NRC**
	0.04	0.18	0.50	1.02	1.04	0.77	0.70

Modified Type D-20 mount – 1" airspace

1/3 Octave Sound Absorption Coefficients at the Octave Band Frequencies							
Frequency (Hz)	**125**	**250**	**500**	**1K**	**2K**	**4K**	**NRC**
	0.17	0.39	0.87	1.10	0.81	0.84	0.80

Modified Type D-50 mount – 2" airspace