



SOUND CURTAINS
BY SOUND SEAL

FLEXIBLE NOISE BARRIERS

SPEC DATA SHEET

B-10 R

REINFORCED FLEXIBLE NOISE BARRIER

A flexible reinforced loaded vinyl barrier designed to reduce the transmission of noise through walls, ceilings and floors, or as a noise barrier component in acoustical composites.

FEATURES:

- Highly durable and suitable for outdoor use
- Limp, flexible, formable, versatile
- High tear and tensile strength
- Nominal Thickness: 0.13"
- Weight 1.0 lb psf
- Tensile (PSI): 1470 lb/in² per ASTM D 638
- Hardness: 85 + 3, shore "A" per ASTM D2240

APPLICATIONS:

- Used in applications where a rugged, tear-resistant noise barrier is required
- Used as a barrier back material in BBC style Acoustical Curtain Panels in acoustical curtain enclosures, acoustical jackets or wraps, or as an accordion-fold acoustical door

B-10 R REINFORCED FLEXIBLE NOISE BARRIER

ACOUSTICAL PERFORMANCE

Sound Absorption Coefficients at the Octave Band Frequencies							
Frequency (Hz)	125	250	500	1K	2K	4K	STC
B-10 R	13	17	22	26	32	37	26

ASTM E-90 & E 413

SIZING

Standard rolls measure 54" x 60' L

AVAILABLE BARRIER COLORS

Gray, Tan, Black, Light Blue*

*subject to availability



SPECIFICATIONS:

Visit www.soundseal.com
or call **1.800.569.1294**

soundseal.com/flexiblebarriers



www.soundseal.com



A CATALYST ACOUSTICS GROUP COMPANY