



**SOUND CURTAINS**  
BY SOUND SEAL

FLEXIBLE NOISE BARRIERS

SPEC DATA SHEET

# **B-20 R**

## REINFORCED FLEXIBLE NOISE BARRIER

A flexible reinforced loaded vinyl barrier designed to reduce the transmission of noise through walls, ceilings and floors, or as a noise barrier component in acoustical composites. B-20 R is also available in a USDA approved grade, or with grommets and Velcro, if desired.

### **FEATURES:**

- Highly durable and suitable for outdoor use
- Limp, flexible, formable, versatile
- High tear and tensile strength
- Nominal Thickness: 0.25"
- Weight 2.0 lb psf
- Tensile (PSI): 1470 lb/in<sup>2</sup> per ASTM D 638

### **APPLICATIONS:**

- Used in applications where a rugged, tear-resistant noise barrier is required
- Used as a barrier back material in BBC style Acoustical Curtain Panels in acoustical curtain enclosures, acoustical jackets or wraps, or as an accordion-fold acoustical door

# B-20 R REINFORCED FLEXIBLE NOISE BARRIER

## ACOUSTICAL PERFORMANCE

Sound Absorption Coefficients at the Octave Band Frequencies							
Frequency (Hz)	125	250	500	1K	2K	4K	STC
B-20 R	16	22	26	32	35	40	31

ASTM E-90 & E 413

## SIZING

Standard rolls measure 54" x 30' L

## AVAILABLE BARRIER COLORS

Gray, Tan, Black, Light Blue\*

\*subject to availability



### SPECIFICATIONS:

Visit [www.soundseal.com](http://www.soundseal.com)  
or call **1.800.569.1294**

[soundseal.com/flexiblebarriers](http://soundseal.com/flexiblebarriers)



[www.soundseal.com](http://www.soundseal.com)



A CATALYST ACOUSTICS GROUP COMPANY