



SOUND CURTAINS
BY SOUND SEAL

EXTERIOR GRADE PANELS

SPEC DATA SHEET



OSP-2

OUTDOOR SOUND PANEL

Sound Seal's **OSP-2** product helps reduce reflection and transmission of unwanted sound waves quickly and easily. Our OSP-2 consists of a 2" thick acoustical fiberglass with exterior grade, UV resistant heavy-duty facings. The OSP-2 is constructed with grommets around the perimeter and are sewn with an exterior-grade thread.

FEATURES:

- Absorb and block unwanted noise in many outdoor applications
- Superior UV and weather resistance
- Easy to handle and install (perimeter grommets for multiple mounting methods)
- Easily cleaned and maintained

APPLICATIONS:

- Construction Sites
- Oil and Gas
- HVAC Equipment
- Dust Collectors
- Anywhere a durable, U/V and weather-resistant product is required
- Commonly installed over fencing or on brick or masonry walls





OSP-2 OUTDOOR SOUND PANEL

ACOUSTICAL PERFORMANCE

Sound Absorption Coefficients at the Octave Band Frequencies							
Frequency (Hz)	125	250	500	1K	2K	4K	STC
OSP-2	7	9	11	21	30	32	18

Sound Absorption Coefficients at the Octave Band Frequencies							
Frequency (Hz)	125	250	500	1K	2K	4K	NRC
OSP-2	0.23	1.20	0.92	0.59	0.15	0.05	0.70

SIZING

2 standard panel sizes are available:

- 54" wide x 104" high
- 54" wide x 54" high
- Can be mounted horizontally or vertically

NOMINAL THICKNESS

- Approximately 2"

WEIGHT

- 0.45lbs. psf.

FIRE RATING

- Class A fire rated per ASTM E84

MATERIAL

- 18 oz VCP facing
- 2" fiberglass batt
- 10 oz taffeta backing

COLOR

- Black (other colors upon request – subject to availability)



SPECIFICATIONS:

Visit www.soundseal.com
or call 1.800.569.1294

soundseal.com/osp



www.soundseal.com | [in](#) [X](#) [v](#) [f](#) [@](#)

 A CATALYST ACOUSTICS GROUP BRAND