

B -20 R Noise Barrier

Sound Seal's B-20 R is a flexible **reinforced** loaded vinyl noise barrier featuring an internal reinforcement to offer maximum tear strength and durability. B-20 R Panels can be used where a noise barrier wall is required. It is also commonly used in conjunction with Sound Seal Quilted Fiberglass Absorbers to form BBC style acoustical curtain composites. B-20 R is also available in a USDA approved grade.



- Rolls are available 54" wide x 30' long
- Curtain Panels available with grommets and Velcro
- Limp, flexible, formable, versatile
- High tear and tensile strength, Extremely durable

Applications:

Typically used where a rugged, tear resistant noise barrier is required. Also used as a barrier back material in BBC style Acoustical Curtain Panels in an Acoustical Curtain Enclosure, acoustical jacket or wrap, and to serve as an accordion fold acoustical door. Suitable for outdoor use. Available in gray, tan, blue or olive.

Product Data:

Description	two pounds per square foot reinforced loaded vinyl barrier
Nominal thickness	0.23 inches
Standard width	54" wide
Roll length	30' long
Weight	2.0 lb psf
Tensile (PSI)	1470 lb/ in ²
Service Temperature	-20° F to +180°

Acoustical Performance:
Sound Transmission Loss

Product	OCTAVE BAND FREQUENCIES (Hz)						
	125	250	500	1000	2000	4000	STC
B-20 R	16	22	26	32	35	40	31

Per ASTM E-90 & E 413

