



SOUND CURTAINS
BY SOUND SEAL

BARRIER BACKED COMPOSITES

SPEC DATA SHEET



VIVID™ BBC-2”

BARRIER BACKED COMPOSITES

Vivid BBC-2” offers the benefits of both a noise barrier and a sound absorber in one composite product. Curtain panels are constructed with grommets across the top and exterior-grade Velcro seals along the vertical edges. Available in bound or unbound rolls, standard panels sizes or custom panels. Add some color to your manufacturing and outdoor spaces with Vivid.

FEATURES:

- Excellent acoustical performance
- Custom sizing
- Easy to install
- Durable, tear and abrasion-resistant
- Great UV and mildew resistance
- Highly water repellent
- Dimensionally stable; will not sag or stretch over time

OUTDOOR APPLICATIONS:

- Construction sites
- Pickle ball / tennis courts
- Outdoor dining venues
- Zoos / animal sanctuaries
- Life span of 10 years in the harshest exterior environments when properly installed

INDOOR APPLICATIONS:

- Music venues
- Manufacturing facilities
- Mechanical enclosures
- Distribution centers



VIVID BBC-2" BARRIER BACKED COMPOSITES

SIZING

- Rolls are available 54" W x 25' L, bound or unbound
- Standard panels 54" x 8' or custom sized panels

WEIGHT

- 1.5# per square foot

FINISHES

- Exterior grade covering
- 12 colors available for face
- 3 colors available for barrier back: light grey, tan or black

THICKNESS/SUBSTRATES

- Standard thickness: 2" thick fiberglass quilt with 1# PSF
- Reinforced mass-loaded vinyl

MOUNTING OPTIONS

- Exterior-grade Velcro seals along vertical edges
- Stainless steel grommets across the top, and bottom, if desired

FIRE RATING

- Class A Flammability Rated per ASTM E- 84
- Flame Spread: 25
- Smoke density: 200

TEMPERATURE RANGE

-20° to +180°F

ACOUSTICAL PERFORMANCE

1/3 Octave Sound Blocking Coefficients at the Octave Band Frequencies

Frequency (Hz)	125	250	500	1K	2K	4K	STC
2" Thickness	14	17	25	38	45	49	29

ASTM E-90 & E 413

1/3 Octave Sound Absorption Coefficients at the Octave Band Frequencies

Frequency (Hz)	125	250	500	1K	2K	4K	NRC
2" Thickness	0.10	0.57	0.83	0.69	0.51	0.37	0.65

ASTM C 423



SPECIFICATIONS:

Visit www.soundseal.com
or call 1.800.569.1294

12 COLORS
AVAILABLE!




soundseal.com/vivid-bbc



www.soundseal.com



 A CATALYST ACOUSTICS GROUP COMPANY