



CHROMA & CHROMA-B

PAINTABLE ACOUSTICAL CEILING TILES

Sound Quality® Ceiling tiles are offered as both a sound absorbing as well as a combination sound absorbing/sound blocking tile.

Chroma Ceiling Tiles have a white fiberglass facing attached to a 1" or 2" thick rigid fiberglass board and have excellent sound absorption (NRC) ratings.

Chroma-B Ceiling Tiles take the standard Chroma tile and add a 1# per square foot foil backed vinyl noise barrier to the backside of the tile for high sound absorption (NRC) and high sound blocking (STC) requirements.

FINISH OPTIONS

Standard Signature White or any Pantone color

CHROMA-PERMEABLE PAINT

Chroma Paintable Ceiling Tiles offers a breathable paint to apply to your Chroma Paintable Ceiling Tiles. Our paint is offered in all Pantone colors and should be applied as recommended in our field painting instructions or call 413.789.1770.

ACOUSTICAL DATA

NRC Rating

1" Thick	_____	.95
2" Thick	_____	1.15
Chroma-B Version	_____	STC 26

SUBSTRATE

6-7# PCF rigid fiberglass core (*Chroma-B adds a vinyl noise barrier)

EDGE DETAIL

Square

WEIGHTS

Chroma Tile .6 lbs/SqFt / Chroma-B Tile 1.6 lbs/SqFt

MOUNTING OPTIONS

Grid supplied by others

SPECIFICATIONS

Specifications can be downloaded from our website www.soundseal.com or call us at **413.789.1770**

- Standard size 2' x 2' or 2' x 4'
- Custom sizes available
- 1" or 2" thickness
- White paintable finish
- Excellent acoustical values
- Offered with a vinyl noise barrier for high STC requirements



50 H.P. Almgren Drive
Agawam, MA 01001

www.soundseal.com

Email: sales@soundseal.com

Tel: 413-789-1770

Fax: 413.789.4444