

SPEC DATA SHEET SQ-115



Sound Quality[®] Ceiling Tiles are offered as both a sound absorbing as well as a combination sound absorbing/sound blocking tile.

C-400 Ceiling Tiles have a black matte facing attached to a 1" or 2" thick rigid fiberglass board and have excellent sound absorption (NRC) ratings.

C-400B Ceiling Tiles take the standard C-400 tile and add a 1# foil backed mass-loaded vinyl to the backside of the tile for high sound absorption (NRC) and high sound blocking (STC) requirements.

FEATURES:

- Black matte facing
- Custom sizes available
- Excellent acoustical values
- Offered with a vinyl noise barrier for high STC requirements

APPLICATIONS:

- Restaurants
- Office spaces
- Schools
- Auditoriums
- Interior adjoining spaces where privacy needs to be added





SIZING

23-¾" x 23-¾" or 23-¾" x 47-¾" to fit into a standard 15/16" ceiling grid

THICKNESS

1" or 2" thicknesses available

WEIGHTS

- C-400 Tile: .75 lbs/square foot (based on 1" thick)
- C-400 B Tile: 1.75 lbs/square foot (based on 1-1/8" thick)

SUBSTRATES

6-7# PCF rigid fiberglass core

* C-400 B adds a vinyl noise barrier

FINISHES

Black matte facing

EDGE DETAIL

Square

MOUNTING OPTIONS

Grid supplied by others



SPECIFICATIONS:

or call 1.800.569.1294

Visit www.soundseal.com

www.soundseal.com

A CATALYST ACOUSTICS GROUP COMPANY