



WOODTRENDS®
BY SOUND SEAL



TIMBER-STIX™

WOOD-VENEERED ACOUSTICAL PANEL



FEATURES

- Quick & easy installation
- Application on walls or ceilings
- Cut to size in field
- Built-in spacers
- Easy to handle
- Linear design
- Choice of 4 woodgrain veneers



SPECIFICATIONS

- **Panel Size:** 24" x 96"
- **Thickness:** 0.87"
- **Weight:** 35 lbs / panel
- **Fire Rating:** Class B per ASTM E-84-21a



INSTALL METHODS

- **Wall:** Furring strip, direct with screws & adhesive
- **Ceiling:** Furring strip



MAKE A STATEMENT.

YOU ONLY GET ONE CHANCE TO MAKE A FIRST IMPRESSION.
WITH TIMBER-STIX, IT'S ALWAYS A GOOD ONE.

COMPOSITION

- **Facing:**
 - Wood-veneered MDF board
- **Backing:**
 - 100% Polyethylene Terephthalate (PET)
 - 55% recycled content

ENVIRONMENTAL FACTORS

- PET is 100% recyclable
- Low VOC emissions
- ASTM — D51116
- LEED — MRc4



VENEER OPTIONS



Light Oak Walnut Dark Oak Grey Oak

ACOUSTICAL DATA

1/3 Octave Sound Absorption Coefficients at the Octave Band Frequencies							
Frequency (Hz)	125	250	500	1K	2K	4K	NRC
	0.08	0.08	0.29	0.70	1.07	0.83	0.55

Type "A" mount – flat

1/3 Octave Sound Absorption Coefficients at the Octave Band Frequencies							
Frequency (Hz)	125	250	500	1K	2K	4K	NRC
	0.04	0.18	0.50	1.02	1.04	0.77	0.70

Modified Type D-20 mount – 1" airspace

1/3 Octave Sound Absorption Coefficients at the Octave Band Frequencies							
Frequency (Hz)	125	250	500	1K	2K	4K	NRC
	0.17	0.39	0.87	1.10	0.81	0.84	0.80

Modified Type D-50 mount – 2" airspace