



SOUND CURTAINS
BY SOUND SEAL

QUILTED FIBERGLASS ABSORBERS

SPEC DATA SHEET



VIVID™ QFA-2”

QUILTED FIBERGLASS ABSORBERS

Vivid QFA-2” consists of a durable indoor/outdoor rated facing quilted to both sides of a 2” thick fiberglass batting. Available in bound or unbound rolls, standard panels or even custom panel sizes. Add some color to your manufacturing and outdoor spaces with Vivid.

FEATURES:

- Excellent acoustical performance
- Custom sizing
- Easy to install
- Durable, tear and abrasion-resistant
- Great UV and mildew resistance
- Highly water repellent
- Dimensionally stable; will not sag or stretch over time
- Light weight

INDOOR/OUTDOOR APPLICATIONS:

- Enclosing HVAC equipment, dust collectors or similar where UV resistance is required
- Installed over fencing or on brick or masonry walls of buildings
- Life span of 10 years in the harshest exterior environments when properly installed.



VIVID QFA-2" QUILTED FIBERGLASS ABSORBERS

SIZING

Rolls are available 48" wide x 25' long, bound or unbound

FINISHES

- Exterior grade facing
- 12 colors available

THICKNESS/SUBSTRATES

- Standard thickness: 2", 1.5 PCF fiberglass core (pre-sewn)
- ACPC facing

THREAD

Stitched with TENARA® thread

WEIGHT

1/2# per square foot

MOUNTING OPTIONS

Stainless steel grommets

FIRE RATING

- Class B Flammability Rated per ASTM E- 84
- Flame Spread: 30
- Smoke density: 250

TEMPERATURE RANGE

-20° to +180°F

ACOUSTICAL PERFORMANCE

1/3 Octave Sound Absorption Coefficients at the Octave Band Frequencies

Frequency (Hz)	125	250	500	1K	2K	4K	NRC
2" Thickness	0.13	0.84	0.92	0.65	0.45	0.30	0.70

Type A Mounting (flat)



SPECIFICATIONS:

Visit www.soundseal.com
or call 1.800.569.1294

12 COLORS
AVAILABLE!



soundseal.com/vivid-qfa



www.soundseal.com



A CATALYST ACOUSTICS GROUP COMPANY