



Made from **92% recycled SBR**
(Styrene-Butadiene Rubber) tire rubber.
Qualifies for up to 5 Leed points.



Vinyl Composition Tile (VCT)
should not be installed over
Probase Vinyl, Jumpax would
be the correct product with VCT

PROBASE VINYL SPECIFICALLY
DESIGNED FOR USE UNDER BOTH
**DRY BACK AND GLUE DOWN LVP/
LVT, SHEET VINYL, CARPET AND
CARPET TILE FLOORING.**

ProBase Vinyl consists of PUR-bonded rubber granules and cork elements and are Green Circle certified for recycled content. ProBase Vinyl is permanently elastic and age resistant for decades for durability under point loads and at only 3mm but will add excellent acoustic improvement to the floor assembly.

- Offers long term performance without collapse or bottoming out
- Suitable for both new construction & renovations
- Quick & easy installation
- Resistant to aging & deformation

SPECIFICATIONS

Material:	Cork/Rubber
Roll Size:	4' x 50' (200 sq ft roll)
Thickness:	3mm
Weight Per Roll:	80 lbs.
Density:	45 lbs./cubic ft
Hardness A Shore Durometer:	45-55
Temperature Resistance:	-40 - 110 c
Sound Reduction:	ΔIIC 22



www.soundseal.com

