

PROBASE VINYL Floor Maintenance

After Installation of the Floor

- Maintain room temperature at 65 degrees Fahrenheit for 48 hours after installation is completed. This assures proper curing, setting and bonding of products.
- The adhesive under your floor needs time to thoroughly dry after installation.
- For vinyl sheet, allow the seams to seal for 8 hours after seam application. This will ensure the proper seam bond and a seamless finish. If seams are disturbed before they're dry, permanent damage may result.

Protection for your Floor

- When moving appliances or heavy furniture, lay a plywood panel on your floor and "walk" the item across it. This protects your floor from scuffing and tears.
- Use Floor Protectors on furniture to reduce indentation. As a general rule of thumb, the heavier the item, the wider the floor protector needed.
- Be careful with rolling casters. They can damage the floor.

General Maintenance

Remove dust and/or vacuuming is a quick and easy way to clear the floor from any dust and "sharp" dirt such as sand. Depending on the use and the desired surface gloss /shine, the floor can (if necessary daily) be cleaned and/or additionally be protected with special vinyl cleaner products recommended by the particular brand of vinyl strips / tiles which have been used.

As for daily cleaning and maintenance.

- Remove dust and sharp dirt regularly with dust wiper and/or vacuum cleaner.
- Remove stains with just a damp (well wringed) cleaning cloth.
- Always avoid the use of excessive water / moisture.

*****Always follow manufactures written instructions for floor maintenance**

