



- Standard size 2' x 2' or 2' x 4'
- Custom sizes available
- 1" or 2" thickness
- Black matte facing
- Excellent acoustical values
- Offered with a vinyl noise barrier for high STC requirements



50 H.P. Almgren Drive  
Agawam, MA 01001

[www.soundseal.com](http://www.soundseal.com)

Email: [sales@soundseal.com](mailto:sales@soundseal.com)

Tel: 800.569.1294

Fax: 413.789.4444

# C-400 & C-400B

## ACOUSTICAL CEILING TILES

Sound Quality® Ceiling tiles are offered as both a sound absorbing as well as a combination sound absorbing/sound blocking tile.

**C-400 Ceiling Tiles** have a black matte facing attached to a 1" or 2" thick rigid fiberglass board and have excellent sound absorption (NRC) ratings.

**C-400B Ceiling Tiles** take the standard C-400 tile and add a 1# per square foot foil backed vinyl noise to the backside of the tile for high sound absorption (NRC) and high sound blocking (STC) requirements.

### FINISH

Black matte facing

### ACOUSTICAL

NRC Rating

1" Thick \_\_\_\_\_ .85

2" Thick \_\_\_\_\_ 1.15

C-400B Version \_\_\_\_\_ STC 26

### SUBSTRATE

6-7# PCF rigid fiberglass core

\*C-400B adds a vinyl noise barrier

### EDGE DETAIL

Square

### WEIGHTS

C-400 Tile .6 lbs/SqFt

C-400B Tile 1.6 lbs/SqFt

### MOUNTING OPTIONS

Grid supplied by others

### SPECIFICATIONS

Specifications can be downloaded from our website

[www.soundseal.com](http://www.soundseal.com) or call us at **1.800.569.1294**